



P2475 PIPE ROLLER FOR 6" - 16" PIPE

Wt/100 pcs: 680 Lbs (308.4 kg)





Material: Cast iron rollers.

• Requires 2 each ½" x ¹⁵/₆" bolts and ½" channel nuts per assembly. Sold separately.

Design Load 1500 Lbs (6.67 kN)

Chart for Dimension A

Pipe	No	Insulation Thickness					
Size	Insulation	1"	1½"	2"	2 ¹ / ₂ "	3"	4"
In	In (mm)	In (mm)	In (mm)	In (mm)	In (mm)	In (mm)	In (mm)
6	9½	101/4	10½	10¾	11	11¾	11 ⁷ / ₈
	241	260.4	267	273	279	289	302
8	10½	*	11	11¾	113/4	12	12½
	257		279	289	299	305	318
10	10¾	*	11%	12	121/4	12½	13
	273		295	305	311	316	330
12	1111/4	*	121//8	12½	123/4	13	13½
	286		308	318	324	330	343
14	11%	*	12½	12 ⁷ / ₈	13	13¾	14
	295		318	327	330	340	356
16	12½	*	13	13¾	131//8	14	14½
	308		330	340	352	356	368

(*Not used for this size)

Standard Dimensions for 1%" (41 mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: $\%\epsilon$ " (14mm); Hole Spacing - From End: $\%\epsilon$ " (21 mm); Hole Spacing - On Center: $1\%\epsilon$ " (48 mm); Width: $1\%\epsilon$ " (41mm); Thickness: $\%\epsilon$ " (6mm)

MATERIAL

Unistrut pipe clamps, unless noted, are punch-press made from hot-rolled, pickled and oiled steel plates, strip or coil, and conform to ASTM specifications A1008, A575, A576, A635, or A36. The fitting steel also meets the physical requirements of ASTM A1011 SS GR 33. The pickling of the steel produces a smooth surface free from scale.

Many items are also available in stainless steel.

Consult factory for ordering information.

FINISHES

Pipe supports are available in:

- Electro-galvanized (EG), conforming to ASTM B633 Type III SC1
- Hot-dipped galvanized (HG), conforming to ASTM A123 or A153 (hardware)
- Perma-Green III (GR), and plain (PL).

Project:		Approval Stamp:		
Architect / Engineer:				
	Phone:			
Contractor:				
Notes 2:				