




CHANNEL NUT WITHOUT SPRING



Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
P3006-0832	#8 -32	6 (2.7)	Any Channel
P3006-1024	#10 -24	6 (2.7)	
P3006-1420	1/4" -20	6 (2.7)	
P3007	5/16" -18	6 (2.7)	
P3008	3/8" -16	9 (4.1)	
P3009	7/16" -14	9 (4.1)	Any Channel Except P3300, P4000, P4100
P3010	1/2" -13	11 (5.0)	
P3013	1/2" -13	8 (3.6)	P3300, P4000 P4100

MATERIAL

Unistrut channel nuts are manufactured from mild steel bars, and after machining operations are completed, they are case hardened, assuring positive biting action into the inturred edge of the Unistrut channel.

Bolt Size	Channel Nut ASTM
1/4" & 5/16"	A1011 SS GR45
3/8", 7/16" & 1/2"	A576 GR1015 Modified
5/8" & 3/4"	A36 or A675 GR60
7/8"	A36

FINISHES

Nuts, bolts and washers are electro-galvanized (EG), ASTM B633 Type III SC1 finish, unless otherwise noted.

Many hardware items are also available in stainless steel. Consult factory for ordering information.

Project: _____ Architect / Engineer: _____ Date: _____ Phone: _____ Contractor: _____ Address: _____ _____ Notes 1: _____ _____ Notes 2: _____ _____	Approval Stamp:
---	--