



CHANNEL NUT WITHOUT SPRINGS



Part Number	Nut Size Thread		Wt/100 pcs Lbs <i>(kg)</i>	Use With
A3006-1420	1⁄4"	-20	5 (2.3)	
A3007	⁵ ⁄16"	-18	5 (2.3)	A1000, A3300, A4000, & A5000
A3008	³ ⁄8"	-16	5 (2.3)	

MATERIAL

Unistrut channels are accurately and carefully cold formed to size from low-carbon strip steel.

STEEL: PLAIN

14 Gauge (1.9 mm), ASTM A1011 SS GR 33 19 Gauge (1.0 mm) ASTM A1008

STEEL: PRE-GALVANIZED

14 Gauge (1.9 mm) ASTM A653 GR 33, 19 Gauge (1.0 mm) ASTM A653 GR 33

Channel nuts are manufactured from mild steel bars conforming to ASTM A576, GR 1015, and are case hardened. Fittings are made from hot rolled, pickled and oiled steel plate or strip and conform to ASTM A1011 SS GR 33.

Many framing channels are available in special metal on request. Consult factory for ordering information.

FINISHES

All channels and fittings are available in: Perma-Green III (GR), Pre-galvanized (PG), conforming to ASTM A653 GR 33 and plain (PL).

Nuts are available in plain or electro-galvanized (EG) finish. Fittings are available in Perma-Green III (GR) or plain (PL).

Project:		Approval Stamp:
	Phone:	
Contractor:		
Notes 1:		
Notes 2:		