


## P1377, P4377, P5077, P5577



Part Number	For Use With	Wt/100 pcs Lbs (kg)
P1377	P1000, P1100, P2000	<b>265</b> <i>120</i>
P4377	P3300, P4000, P4100	176 80
P5077	P5000	390 177
P5577	P5500	310 141

Standard Dimensions for 15/8" (41mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 11/8" (14mm); Hole Spacing - From End: 13/8" (21mm); Hole Spacing - On Center: 11/8" (48mm); Width: 15/8" (41mm); Thickness: 1/4" (6mm)

## **MATERIAL**

Fittings, unless noted, are made from hot-rolled, pickled and oiled steel plates, strip or coil, and conform to ASTM specifications A575, A576, A635, or A36. The fitting steel also meets the physical requirements of ASTM A1011 SS GR 33. The pickling of the steel produces a smooth surface free from scale.

Many fittings are also available in stainless steel, aluminum and fiberglass. Consult factory for ordering information.

## **FINISHES**

Fittings are available in:

Perma-Green III (GR),

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1;

Hot-dipped galvanized (HG), conforming to ASTM A123 or A153 and

Plain (PL).

Project:		
	Phone:	
	Filolie	
Notes 1:		
Notes 2:		