

# MATERIAL SAFETY DATA SHEET

## STEEL PRODUCTS

CODE NO. N/A  
 ORIGINAL ISSUE DATE: 4/7/2014 REVISED -

<b>I. IDENTIFICATION</b>	<b>INFORMATION &amp; EMERGENCY TELEPHONE NUMBERS</b> (708) 339-1610
PRODUCT NAME: UNISTRUT DEFENDER  COMMON NAME(S): METAL FRAMING STRUT  PRODUCTS AFFECTED: 1) CHANNEL (STRUT) 2) PIPE CLAMPS (EXCEPT HARDWARE) 3) CONCRETE INSERTS (P3200 & P3300)	<b>MANUFACTURER:</b> UNISTRUT INTERNATIONAL 16100 SOUTH LATHROP AVE. HARVEY, IL 60426

**II. INGREDIENTS AND RECOMMENDED OCCUPATIONAL EXPOSURE LIMITS**

Note: Steel Products under normal conditions do not present an inhalation, ingestion or contact health hazard (see Section VI)

BASE METAL, ALLOYING ELEMENTS AND METALLIC COATINGS	% WEIGHT	EXPOSURE LIMITS	
		OSHA PEL	ACGIH TLV (1992-1993)
Base Metal: Iron	95.1 – 99.8	10 mg/M <sup>3</sup> as Fe <sub>2</sub> O <sub>3</sub> Fume	5 mg/M <sup>3</sup> as Fe <sub>2</sub> O <sub>3</sub> Fume
Manganese	< 0.5	5 mg/M <sup>3</sup>	1 mg/M <sup>3</sup> as Fume
Zinc	0.2 ~ 4.0	5 mg/M <sup>3</sup> as ZnO Fume	5 mg/M <sup>3</sup> as ZnO Fume
Aluminum	0.01 ~ 0.30	None Listed	10 mg/M <sup>3</sup>
Magnesium	0.01 ~ 0.10	15 mg/M <sup>3</sup> as Oxide Fume	10 mg/M <sup>3</sup>

Note:

- 1) These products contain trace quantities of various elements but not at reportable levels under the OSHA Hazard Communication Standard Limit (29 CFR 1910.1200).
- 2) The weight of additional coating film shall be 0.001% or less of total product weight.

**III. PHYSICAL DATA**

<b>MELTING POINT</b>	<b>APPEARANCE and ODOR</b>	<b>Metallic Luster</b> No Odor
<b>BASE METAL:</b> > 2,550 °F <b>METALLIC COATING:</b> > 570 °F		

**IV. FIRE AND EXPLOSION HAZARD DATA**

STEEL PRODUCTS IN THE SOLID STATE PRESENT NO FIRE OR EXPLOSION HAZARD.

**V. REACTIVITY DATA**

Stable under normal conditions of use, storage and transport.

**VI. HEALTH HAZARD DATA**

NOTE: Steel products under normal conditions do not present an inhalation, ingestion, or contact health hazard. However, operations such as burning, welding, sawing, brazing, grinding, and possibly machining, etc., which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, may present health hazards.

EFFECTS OF OVEREXPOSURE:      **MAJOR EXPORSURE HAZARD**

<input checked="" type="checkbox"/> INHALATION	<input type="checkbox"/> SKIN CONTACT	<input type="checkbox"/> EYE CONTACT	<input type="checkbox"/> INGESTION
--	---------------------------------------	--------------------------------------	------------------------------------

Chronic inhalation of high concentrations of iron oxide fumes or dusts may lead to a benign pneumoconiosis (siderosis).  
 Inhalation of high concentrations of ferric oxide may possibly enhance the risk of lung cancer development in workers exposed to

pulmonary carcinogens.

The inhalation of high concentrations of freshly formed oxide fumes and dusts of Manganese, Copper, Lead and/or Zinc in the respirable particle size range can cause an influenza-like illness termed metal fume fever. Typical symptoms last 12 to 48 hours and are characterized by metallic taste in the mouth, dryness and irritation of the throat, followed by weakness, muscle pain and chills. No long-term effects of metal fume fever have been noted.

#### EMERGENCY AND FIRST AID PROCEDURES

For overexposure to airborne fumes and particulates, remove exposed person to fresh air. If breathing is difficult or has stopped, administer artificial respiration or oxygen as indicated. Seek medical attention promptly.

Treat metal fume fever by bed rest, and administer a pain and fever reducing medication.

#### VII. SPILL OR LEAK PROCEDURES

NOT APPLICABLE TO STEEL IN THE SOLID STATE.

#### VIII. SPECIAL PROTECTION INFORMATION

**RESPIRATORY:** For welding or burning – **NIOSH/MSHA** – approved dust and fume respirators should be used to avoid excessive inhalation of particulates. Appropriate respirator selection depends on the magnitude of exposure.

**SKIN:**

Protective gloves should be worn as required for welding, burning or handling operations.

**EYE:**

Use safety glasses or goggles as required for welding, burning, or handling operations.

**VENTILATION:** Local exhaust ventilation should be provided when sawing, grinding or machining to prevent excessive dust or fume exposure. During welding, burning or brazing please follow the ANSI Standard Z49.1 "Safety in Welding and Cutting".

#### OTHER PROTECTIVE EQUIPMENT:

Depending upon the conditions of use and specific work situations, additional protective equipment and/or clothing may be required to control exposures.

#### IX. SPECIAL PRECAUTIONS

##### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE.

Operations with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Avoid breathing metal fumes and/or dusts.

##### OTHER COMMENTS:

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Individuals with chronic respiratory disorders (i.e.: asthma, chronic bronchitis, emphysema, etc.) may be adversely affected by any fume or airborne particulate matter exposure.

THIS INFORMATION IS TAKEN FROM SOURCES OR BASED UPON DATA BELIEVED TO BE RELIABLE; HOWEVER, ALLIED TUBE & CONDUIT CORPORATION MAKES NO WARRANTY AS TO THE ABSOLUTE CORRECTNESS OR SUFFICIENCY OF ANY OF THE FOREGOING OR THAT ADDITIONAL OR OTHER MEASURES MAY NOT BE REQUIRED UNDER PARTICULAR CONDITIONS.