



**DEWALT**®

ENGINEERED BY **Powers**™

## Overhead Anchoring

- 3/4" Embedment
- Flush Mounted
- Internally Threaded
- For Cracked and Uncracked Concrete

### CODE LISTED

ICC-ES ESR-3912

CRACKED & UNCRACKED  
CONCRETE

**Mini-Undercut+**™



# DEWALT®

ENGINEERED BY **Powers™**

Post Tension Concrete



Hollow Core Concrete



**CODE APPROVED**  
3/4" long approved seismic anchor

**PATENT PENDING GEOMETRY**  
patent pending design bites into concrete for undercut

**STOP BIT**  
widened shoulder eliminates potential for over drilling; solid carbide head for quick drilling



**SDS SETTING TOOL BIT**  
for fast installation

**THREADED SLEEVE**  
internally tapped sleeve provides full thread engagement



## Mini-Undercut+™ Internally Threaded Undercut Anchor



### Mini-Undercut+

CATALOG NUMBER	ANCHOR SIZE	ROD DIA	DRILL DIA	QTY	MASTER QTY
PFM2111820	3/8" x 3/4"	3/8"	5/8"	100	600

CATALOG NUMBER	USE ACCU-BIT	USE SDS SETTING TOOL
PFM2111820	PPA2431720	PFM2101720

### Accu-Bit

CATALOG NUMBER	STOP BIT SIZE	ROD DIA	DRILL DIA	DRILL DEPTH	QTY
PPA2431720	5/8" x 3/4"	3/8"	5/8"	3/4"	1

### SDS Setting Tool

CATALOG NUMBER	SETTING TOOL SIZE	ROD DIA	QTY
PFM2101720	5/8" x 3/4"	3/8"	1

### Installation Systems

CATALOG NUMBER	DESCRIPTION
DCH273P2	20V MAX XR Brushless 1" L-shape SDS Plus Rotary Hammer Kit 

Dealer Stamp

1-800-4 **DEWALT**

www.**DEWALT**.com